



KINOTECHNIKA



RUBIKORE

IN ADMIRATION OF MUSIC




ΚΩΔΙΚΟΣ / EAN		ΠΕΡΙΓΡΑΦΗ	ΛΙΑΝΙΚΗ ΜΕ ΦΠΑ
<p>RUBIKORE On Wall</p> <p>White High Gloss Black High Gloss Natural Walnut</p>		<p style="text-align: center;">RUBIKORE On Wall</p> <p>Frequency range 59 - 34,000 Hz ±3 dB Sensitivity (dB) 88.5 dB @ 1 m for 2.83 V Impedance Ω 4 Maximum SPL (dB) 108 Recom.Power(Watt) 20 - 150 High Frequency drivers 17 x 45 mm planar magnetostatic tweeter 1 x 29 mm low loss soft dome Low/Mid Frequency drivers 1 x 6½ inch Enclosure Type Bass Reflex Dimension(HxWxD) cm 46,5 x 27,8 x 14,2 Weight (kg) 8.5 (Χρώματα:Black High Gloss, White High Gloss,Natural Walnut)</p>	<p style="text-align: center;">1.499 €</p>
<p>RUBIKORE CINEMA</p> <p>White High Gloss Black High Gloss Natural Walnut</p>		<p style="text-align: center;">RUBIKORE CINEMA</p> <p>Frequency range 38 - 34,000 Hz ±3 dB Sensitivity (dB) 88.5 dB @ 1 m for 2.83 V Impedance Ω 4 Maximum SPL (dB) 110 Recom.Power(Watt) 40 - 200 High Frequency drivers 17 x 45 mm planar magnetostatic tweeter 1 x 29 mm low loss soft dome Low/Mid Frequency drivers 2 x 6½ " " " " " " Enclosure Type Bass Reflex Dimension(HxWxD) cm 99 x 20 x 38 Weight (kg) 23 (Χρώματα:Black High Gloss, White High Gloss, Maroon High Gloss, Natural Walnut)</p>	<p style="text-align: center;">1.999 €</p>

KINOTECHNIKA



RUBIKORE

IN ADMIRATION OF MUSIC

		ΠΕΡΙΓΡΑΦΗ	ΛΙΑΝΙΚΗ ΜΕ ΦΠΑ
RUBIKORE 8 White High Gloss Black High Gloss Maroon High Gloss Natural Walnut		RUBIKORE 8 Frequency range 38 - 34,000 Hz ±3 dB Sensitivity (dB) 90.5 dB @ 1 m for 2.83 V Impedance Ω 4 Maximum SPL (dB) 112 Recom.Power(Watt) 40 - 250 High Frequency drivers 17 x 45 mm planar magnetostatic tweeter 1 x 29 mm low loss soft dome Low/Mid Frequency drivers 3 x 6½ " Enclosure Type Bass Reflex Dimension(HxWxD) cm 110 x 22 x 44,5 Weight (kg) 30 (Χρώματα:Black High Gloss, White High Gloss, Maroon High Gloss, Natural Walnut)	6.998 €
RUBIKORE 6 White High Gloss Black High Gloss Maroon High Gloss Natural Walnut		RUBIKORE 6 Frequency range 38 - 34,000 Hz ±3 dB Sensitivity (dB) 88.5 dB @ 1 m for 2.83 V Impedance Ω 4 Maximum SPL (dB) 110 Recom.Power(Watt) 40 - 200 High Frequency drivers 17 x 45 mm planar magnetostatic tweeter 1 x 29 mm low loss soft dome Low/Mid Frequency drivers 2 x 6½ " Enclosure Type Bass Reflex Dimension(HxWxD) cm 99 x 20 x 38 Weight (kg) 23 (Χρώματα:Black High Gloss, White High Gloss, Maroon High Gloss, Natural Walnut)	4.998 €
RUBIKORE 2 White High Gloss Black High Gloss Maroon High Gloss Natural Walnut		RUBIKORE 2 Frequency range [Hz] 50 - 26,000 Hz ±3 dB Sensitivity (dB) 87 dB @ 1 m for 2.83 V Impedance Ω 4 Recom.Power(Watt) 40 - 150 Low/Mid Frequency drivers 1 x 6½ inch High Frequency drivers 1 x 29 mm low loss soft dome Dimension(HxWxD) 350 x 195 x 335 mm Weight (kg) 9.5	2.598 €